

DETERMINATION OF PARTICLE SIZE DISTRIBUTION BY SIEVING (GRAIN SIZE ANALYSIS)

Aim: To determine the particle size distribution by sieving (Grain size analysis) and to determine the fineness modulus, effective size and uniformity coefficient.

This test is performed to determine the percentage of different grain sizes contained within a soil. The mechanical or sieve analysis is performed to determine the distribution of the coarser, larger-sized particles. The distribution of different grain sizes affects the engineering properties of soil. Grain size analysis provides the grain size distribution, and it is required in classifying the soil.

Specifications:

This test is specified in IS: 2720 (Part 4) – 1985 (Reaffirmed-May 2015) – Method of test for soil (Part 4- Grain size analysis). (Note: Depends of standart)

Equipments Required:

- a) Sieves of sizes: 4.75 mm, 2.0 mm, 1.0 mm, 600 μ , 300 μ , 150 μ and 75 μ . That is, I.S 460-1962 is used. The sieves for soil tests: 4.75 mm to 75 microns. (Depends of standart)
- b) Thermostatically controlled oven.
- c) Trays, sieve brushes, mortar with a rubber covered pestle, etc.
- d) Mechanical sieve shaker etc.

Theory:

The grain size analysis is widely used in classification of soils. The data obtained from grain size distribution curves is used in the design of filters for earth dams and to determine suitability of soil for road construction, air field etc. Information obtained from grain size analysis can be used to predict soil water movement although permeability tests are generally used. The method is applicable to dry soil passing through 4.75 mm size sieve less than 10 % passing through 75-micron sieve.

Sorumlu Akademisyen: Prof. Dr. Izzet KARAKURT

Deney Sorumlusu: Ars. Gor. Yunus ISKENDER

TRABZON- 2023

KARADENİZ TEKNİK ÜNİVERSİTESİ
MADEN MÜHENDİSLİĞİ BÖLÜMÜ
MINE3003 – ZEMİN MEKANİĞİ LAB.

Percentage retained on any sieve = (weight of soil retained / total weight) x 100

Cumulative percentage retained = sum of percentages retained on any sieve on all coarser sieves

Percentage finer than any sieve = 100 percent minus cumulative Size, N Percentage retained.

Precautions:

- Clean the sieves set so that no soil particles were struck in them
- While weighing put the sieve with soil sample on the balance in a concentric position.
- Check the electric connection of the sieve shaker before conducting the test.
- No particle of soil sample shall be pushed through the sieves.

Procedures:

- a) Take a representative sample of soil received from the field and dry it in the oven.
- b) Use a known mass of dried soil with all the grains properly separated out.
The maximum mass of soil taken for analysis may not exceed 500 g.
- c) Prepare a stack of sieves. Set the sieves one over the other with an ascending order (sieves having larger opening sizes i.e., lower numbers are placed above the one with smaller opening sizes i.e., smaller numbers). The very last sieve is #200 (75 μ sieve). A pan is attached to the lowest 75 μ sieve to collect the portions passing #200 sieves and fit the nest to a mechanical shaker.
- d) Make sure sieves are clean. If many soil particles are stuck in the openings try to poke them out using brush.
- e) The whole nest of sieves is given a horizontal shaking for 10 min in sieve shaker till the soil retained on each reaches a constant value.
- f) Determine mass of soil retained on each sieve including that collected in the pan below.

The test results obtained from a sample of soil are given below. Mass of soil taken for analysis $W =$ _____ gr.

Sorumlu Akademisyen: Prof. Dr. İzzet KARAKURT

Deney Sorumlusu: Ars. Gor. Yunus ISKENDER

TRABZON- 2023

KARADENİZ TEKNİK ÜNİVERSİTESİ
MADEN MÜHENDİSLİĞİ BÖLÜMÜ
MINE3003 – ZEMİN MEKANİĞİ LAB.

Elek Analizi Deneyi Laboratuvar Sonuçları:

ELEK ANALİZİ						
Elek No	Elek Açıklığı (mm)	Elek Ağırlığı (gr)	Elek Ağırlığı+ Elek Üzerinde Kalan Zemin (gr)	Elekte Kalan Zemin (gr)	Elekten Geçen Zemin (gr)	Elekten Yüzde Geçen (%)
4	4.75					
10	2.00					
18	1.00					
30	0.600					
50	0.300					
100	0.150					
200	0.075					
TEPSİ						

Toplam örnek ağırlığı $W' = \text{-----}$ gr



Yatay Eksen: Tane Boyutu (mm)
Düşey Eksen: Yüzde Geçen (%)

Sorumlu Akademisyen: Prof. Dr. İzzet KARAKURT

Deney Sorumlusu: Ars. Gor. Yunus ISKENDER

TRABZON- 2023

KARADENİZ TEKNİK ÜNİVERSİTESİ
MADEN MÜHENDİSLİĞİ BÖLÜMÜ
MINE3003 – ZEMİN MEKANİĞİ LAB.

Sorular:

- 1) Tane boyutu analizini tanımlayınız ve silt boyutu nedir? (10p)
- 2) Üniformluk katsayısı C_u nedir? Nasıl hesaplanır? (10p)
- 3) Zemin için D10, D30 ve D60, elek analizi ile nasıl hesaplanır? (10p)
- 4) C_c ve C_u değerlerini hesaplamak için kullanılan formülleri yazınız. (10p)
- 5) Kötü derecelenmiş ve iyi derecelenmiş zemin nedir? Kısaca açıklayınız. (10p)

Üniformluk Katsayısı, C_u =

Süreklilik Katsayısı, C_c =

- 6) Yarı logaritmik kağıt kullanarak tane boyut dağılımı grafiğini çiziniz. Grafiği kullanarak, numunenin %10, %30 ve %60 'ının geçtiği tane çaplarını elde edin; bunlar D10, D30, D60 'tır. Bunları kullanarak zeminin ne kadar iyi derecelendirildiğini, yani zeminin iyi derecelendirilmiş olup olmadığını gösteren C_c ve C_u 'yu hesaplayınız. Zemin sınıfını grafiği kullanarak tayin ediniz. (45p)

(X= Öğrenci numarasının son rakamı)

ELEK ANALİZİ						
Elek No	Elek Açıklığı (mm)	Boş Elek Ağırlığı (gr)	Elek Ağırlığı + Elekte Kalan Zemin (gr)	Elekte Kalan Zemin (gr)	Elekten Geçen Zemin (gr)	Elekten Yüzde Geçen (%)
4	4.75	1000	11X0			
10	2.00	1000	113X			
18	1.00	1000	108X			
30	0.600	1000	11X5			
50	0.300	1000	10X5			
100	0.150	1000	110X			
200	0.075	1000	105X			
TEPSİ		1000	1070			

Not: 5 puan raporun düzenine göre verilecektir.

Sorumlu Akademisyen: Prof. Dr. İzzet KARAKURT

Deney Sorumlusu: Ars. Gor. Yunus ISKENDER

TRABZON- 2023